

NEW TRANSMISSION OIL ATF ULV

TRANSMISSION OIL | 29001

Low viscosity automatic transmission fluid with excellent wear protection.

Suitable for American transmissions:

Ford	6-speed transmission 6F15 8-speed automatic transmission 8F24, 8F35, 8F40, 8F57
GM	10-speed 10R60, 10R80-MHT, 10R80, 10R140 10-speed 10L80 MF6, 10L90 MGL, 10L100 (Allison) MGM/MGU

Suitable for Aisin-Warner transmissions:

8-Gang Aisin	AWF8G30, AWF8G35, AWF8G45, AWF8G55
BMW	GA8F22AW
Citroën	EAT8
Mini	GA8F22AW
Peugeot	ATN8
Toyota	Direct Shift-8AT
Volvo	AWF8G45
VW	09S (AQ300-8F)

Recommendations:

ATF	AW-2
BMW/Mini	83 22 2 413 477, ATF 7, GA8F22AW, Cooper CVT
Citroën	EAT8
Ford	Mercon ULV, WSS-M2C949-A
PSA	16 350 560 80
Volvo	31492172, 31492173
VW	G 053 001 A2, G 060 540



Content	VPE	Pallet	VAICO No
1 l	12	600	V60-0310

More containers on request.

* For detailed vehicle information, please refer to the vehicle lists under www.vierol-shop.de. Our general terms and conditions of sale and delivery as well as our warranty conditions apply, which are available for download on our website. Errors excepted. Reference numbers and names, with the exception of VIEROL AG, are for comparison only and may not be disclosed in invoices. They are non-binding and no indication of origin. © VIEROL AG